

CHARACTERISTICS	UNIT	KRMG
Printing speed (max)	mm/s	80
Printing width	mm	48
Resolution	dot/mm	8
Number of dots	dot	384
Columns	column	24/42
Character size	dot*dot	16*24 - 9*24
Resident code page	---	CP437
Bar code type	---	Interleaved 2/5, UPC-A & UPC-E, JAN 8 (EAN8) & JAN 13 (EAN13), Code 39, 93 & 128, Codabar, PDF417
Paper width	mm	60
Paper roll diameter	mm	120
Paper thickness	µm	60 to 80
Paper loading	---	Auto loading
Operating voltage	VDC	12-24
Power consumption	W	55
Head pulse life	pulse	1*10 ⁶
Mechanical reliability	km	50
Dimensions (W*D*H)	mm	125*168*112
Weight	g	1525
Operating temperature	°C/F	0 to 50/32 to 122
Operating humidity	%RH	20 to 85 (non condensing)
Cutter	---	Auto cutter, full and/or partial cut
Cutter life	cut	1 million
Data buffer	Kbytes	4
Flash Memory extension	Mbytes	-
RAM Memory extension	Kbytes	-
Interface	---	RS232 or parallel IEEE 1284 (with sub - D25 connector)
Driver	---	Windows™ 98/00/XP
CEM & Safety standards	---	UL60950, CSA 22.2-60950, IEC60955, CE Class B, FCC part 15 class B, C-Tick
Sensors	---	Paper low, paper out
Accessories	---	Power supply