

CHARACTERISTICS	UNIT	TPOS
Printing speed (max)	mm/s	100
Printing width	mm	56
2 color print capability	---	NO
Resolution	dot/mm	8
Number of dots	dot	448
Number of columns	column	28 or 37
Character size	dot*dot	12*24 or 16*24
Resident code page	---	CP437/858
Bar code type	---	Interleaved 2/5, UPC-A, UPC-E, JAN8 (EAN8) & JAN13 (EAN13), Code 39&128
Paper width	mm	58
Paper roll diameter	mm	90
Paper thickness	µm	80 (with tear bar), 65 (with auto cutter)
Paper loading	---	Clamshell™
Operating voltage	VDC	24
Current consumption	A	2.5
Head pulse life	pulse	1*10 ⁸
Mechanical reliability	km	100
Dimensions (W*D*H)	mm	121*180*124
Operating temperature	°C/F	0 to 50/32 to 122
Operating humidity	%RH	10 to 90
Cutter	---	Auto cutter (full or partial cuts) or manual tear bar
Cutter life	cuts	1 million
Data buffer	Kbyte	1
Flash Memory	Kbytes	64
Interface	---	RS232&USB
Driver	---	Windows™ 98/00/XP
Emulation	---	ESC/POS™
CEM & Safety standards	---	UL/CAS60950, IEC/EN60950, CE Class A, FCC Class A, C-Tick
Added features	---	1 CDKO, Buzzer, Fixation hole for wall mounting
Accessories	---	Powered USB cable