

HTPx/CHTx

60 mm



CLAMSHELL™



60 mm

Key features

- Integrated paper bucket
- Compact design
- Easy to integrate

Controller Boards

- Minicont 5V
- TPSB
- Minicont Para
- License agreement

CHARACTERISTICS	UNIT	CHTN9050 HTPN9050	HTP-9012	CHTP9024 HTP-9024
Printing speed (max)	mm/s	50	75	100
Printing width	mm		48	
Resolution	dot/mm		8	
Number of dots	dot		384	
Paper width	mm		60	
Paper thickness	µm		60-80	
Paper loading	---		Clamshell™	
Operating voltage range : logic dots	V	4.5-7	5 (+/-5%) 10-15.2	20-26.4
Head pulse life	pulse		1*10 ⁸	
Mechanical reliability	km		50	
Dimensions (W*D*H)	mm	92.8*76*55 (HTPx)		74.6*43.6*45.7 (CHTx)
Weight	g	150 (HTPN), 130 (CHTN)	150	150 (HTP), 130 (CHTP)
Operating temperature	°C/F		0 to 50/32 to 122	
Cutter	---		Manual tear bar	
Compatible board	---	Minicont 5	I	Minicont Para, TPSB
Options	---		Cover with latch for HTP versions	
Added features	---		Bucket included for HTP versions	