



KRMG

60 mm

Key features

- Compact and rugged design
- 'No spindle' concept
- Easy to integrate
- Low and easy maintenance



CUTTER



60 mm

CHARACTERISTICS	UNIT	KRMG
Printing speed (max)	mm/s	90
Printing width	mm	48
Resolution	dot/mm	8
Number of dots	dot	384
Columns	column	24/42
Character size	dot*dot	16*24 - 9*24
Resident code page	---	CP437
Bar code type	---	Interleaved 2/5, UPC-A & UPC-E, JAN 8 (EAN) & JAN 13 (EAN), Code 39, 93 & 128, Codabar, PDF417
Paper width	mm	60
Paper roll diameter (max)	mm	120
Paper thickness	µm	60-80
Paper loading	---	Auto loading
Operating voltage range	V	10 to 15.2 - 20 to 26.2
Current consumption	A	2.5 (average) - 13 (peak)
Head pulse life	pulse	1*10 ⁸
Mechanical reliability	km	50
Dimensions (W*D*H)	mm	125 (140)*174*130 (with paper roll)
Weight	g	1525
Operating temperature	°C/F	0 to 50/32 to 122
Cutter	---	Auto cutter, full and/or partial cut
Cutter life	cut	1 million
Data buffer	KBytes	4
Interface	---	RS232 or parallel IEEE 1284 (with sub -DB25 connector) or USB
Driver	---	Windows™ 98/00/XP
Safety standards	---	UL, CE, FCC
Sensors	---	Paper low, paper out
Options	---	Power supply